

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 253 562 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
30.10.2002 Bulletin 2002/44

(51) Int Cl.7: G07F 11/42, G07F 11/32

(21) Application number: 02076211.8

(22) Date of filing: 28.03.2002

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: Nicolini, Antonio
36015 Schio, Vicenza (IT)


(74) Representative: Martegani, Franco
Franco Martegani S.r.l.
Via Carlo Alberto, 41
20052 Monza (Milano) (IT)

(30) Priority: 05.04.2001 IT MI010727

(71) Applicant: Officine Meccaniche F.lli Manea S.r.l.
36010 Zane' (Vicenza) (IT)

(54) **Controlled output automatic product dispensing machine**

(57) A controlled output automatic product dispensing machine, comprising a fixed structure (13) with at least one shelf (10) holding at least one product-carrying drawer (11) and with at least one door (12) to collect the selected product. Said machine provides at least one guide (15) to slide a container (14) which collects the selected product near the corresponding product carrying drawer (11) and moves it to a collecting position accessible to the user after opening the door (12).

**Fig.2**

bruu → . Stockage étagé
• ascenseur f → bac/chute
• orifice sortie avec
plaque anti-effort
• moyen d'arrivée de
produit

EP 1 253 562 A1

THIS PAGE BLANK (USPTO)

(D1)

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 253 562 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
30.10.2002 Bulletin 2002/44

(51) Int Cl.7: G07F 11/42, G07F 11/32

(21) Application number: 02076211.8

(22) Date of filing: 28.03.2002

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: Nicolini, Antonio
36015 Schio, Vicenza (IT)

(74) Representative: Martegani, Franco
Franco Martegani S.r.l.
Via Carlo Alberto, 41
20052 Monza (Milano) (IT)

(30) Priority: 05.04.2001 IT MI010727

(71) Applicant: Officine Meccaniche F.lli Manea S.r.l.
36010 Zane' (Vicenza) (IT)

(54) Controlled output automatic product dispensing machine

(57) A controlled output automatic product dispensing machine, comprising a fixed structure (13) with at least one shelf (10) holding at least one product-carrying drawer (11) and with at least one door (12) to collect the selected product. Said machine provides at least one guide (15) to slide a container (14) which collects the selected product near the corresponding product carrying drawer (11) and moves it to a collecting position accessible to the user after opening the door (12).




Fig.2

EP 1 253 562 A1

Description

[0001] This invention refers to a controlled output automatic product dispensing machine.

[0002] For large-volume packaged consumer products, such as cans, bottles, foodstuffs, pharmaceuticals and the like, automatic machines are available for dispensing said products after a user's selection and subsequent payment.

[0003] At this time and following the user's selection and payment of a certain available product, these machines internally locate the chosen product, which is arranged in an appropriate drawer of an internal shelf of the machine. The machine then allows it to drop by gravity into an underlying collecting pocket, whence the user retrieves it by hand.

[0004] The pocket is closed by an openable door, such as for instance a push-in door, and provides for a simple anti-intrusion system preventing a manual access to the dispenser's internal drawers.

[0005] In the described system, the products paid out from the topmost internal drawers, especially those of a more delicate nature, may obviously encounter considerable dispensing problems.

[0006] In addition to the possible jamming of the selected product during its descent, there's a risk of damaging the product itself, glass bottles for instance, due to its falling height.

[0007] Moreover, even cans of carbonated drinks suffer some considerable shaking-up while falling, so that at their subsequent opening the internally compressed gas induces a partial spillage of the beverage.

[0008] The general purpose of this invention is to prevent the uncontrolled payout of the products dispensed by an automatic machine, which may jam while falling toward the collecting pocket, or suffer damage while falling into the collecting pocket itself.

[0009] Another purpose is to develop an anti-intrusion system in the collecting pocket, capable of preventing the access to the product carrying drawers.

[0010] In view of the mentioned purposes according to this invention, it was decided to produce a controlled output automatic product dispensing machine with the characteristics outlined in the attached claims.

[0011] The structural and functional characteristics of this invention and its advantages in comparison to the known art will become even clearer and better evident from a review of the following description in reference to the attached drawings, which illustrate a transport system in accordance with the innovative principles of the invention.

[0012] In the drawings:

- Figure 1 offers an overall axonometric view of a first embodiment of this invention, which shows a top-side sliding container in a dispensing position facing a product-carrying drawer, and a bottomside collecting pocket accessible by a user through a prod-

uct collecting door;

- Figure 2 is a side view of Figure 1,
- Figure 3 is an enlarged axonometric view of a detail of Figure 1, precisely a self-lubricating block linked to a guide and a belt,
- Figure 4 is a partial and enlarged side view of Figure 1, showing the sliding container near a product collecting position,
- Figure 5 offers a side view of an enlarged detail of Figure 4, showing a door blocking system in a blocking position,
- Figure 6 offers a side view of the same enlarged detail of Figure 5, but at a condition in which the container is in a collecting position; in this position the blocking system turns out to be unblocked.

[0013] With reference to the mentioned figures, these show an automatic dispensing machine fitted with a unit for transporting the products from the dispensing point next to a product carrying drawer to the collecting point next to the collecting door, according to this invention.

[0014] An automatic dispensing machine offers one or more shelves 10, each being fitted with at least one product carrying drawer 11.

[0015] Whenever a product is selected, the machine identifies the product carrying drawer 11 containing it, and allows it to drop by an expelling system, into the collecting area which is accessible through a door 12. Said door 12 is firmly attached to the machine's fixed structure 13, as shown in Figures 1 and 2.

[0016] The machine's fixed structure 13, precisely the area facing the product-carrying drawers 11, in the space where the selected products fall into the collecting area, mounts a unit for transporting the products from the dispensing point next to a product carrying drawer to the collecting point set behind the door 12.

[0017] Said unit is essentially composed of a sliding container 14 set in front of the selected product carrying drawer 11, receives the product and moves it behind the door 12 to be collected: the Figures 1 and 2 show the sliding container 14 in the two mentioned positions.

[0018] The motion of the container 14 occurs along two guides 15 which are attached to the lateral walls of the dispensing machine.

[0019] Each of said guides 15 holds a sliding block 16 made of a self-lubricating material, for instance polythene, which is laterally attached to the container 14.

[0020] On the block 15, the two extremities of a belt 17 are attached while being hooked up in a ring between the two pulleys 21, for instance two punched platelets 18, as shown in Figure 3.

[0021] One of the two belts 17 is controlled by an electric motor 19 and by the relative pulleys; the other belt 17 is shifted in a synchronous manner by the rotating shaft 20, which is linked to the motor 19 by a pulley.

[0022] The rotation of the shaft of the electric motor 19 thus ultimately controls the vertical motion of the container 14, by shifting the two belts 17 which simultane-

ously shift the two blocks 16 over the guides 15. The container 14 can therefore position itself opposite the various shelves 10 and into the collecting position behind the door 12.

[0023] The motion of the container 14 thus looks like the motion of a lift moving in a vertical manner with respect to the machine.

[0024] Considering that the various shelves 10 of the product-carrying drawers 11 may be set apart at a variable distance depending on the products charged, the container 14 is fitted with a small hall-effect probe 34 to detect the position of the shelves 10. This occurs by touch-activating the probe 34 by a magnet 35 positioned on each shelf 10, as shown in Figure 2.

[0025] In this manner the machine managing program receives the information about the position of the container 14.

[0026] The guides 15 are moreover equipped with an upper and a lower stop. Starting from the lower stop, which sets the reference collecting position of the container 14, the machine managing program can, through the probe 34 mounted on the container 14, detect the position of the shelf 10 identified by the magnet 35, where it should position itself to receive the selected product and whence it should subsequently revert to the collecting point.

[0027] The container 14 is also equipped with an anti-intrusion mechanism 40, as shown in Figure 4.

[0028] It comprises a front door 22 hinged to the container 14 by a pin 23, and a rear door 24 hinged to the container 14 by a pin 25.

[0029] The two doors 22 and 24 are connected by two arm-shaped elements 26 and 27 joined by a pin 28.

[0030] In order to collect the product dropped into the container 14 after reaching its collecting position, the door 12 must be pushed in. This action involves lifting the door 22. Through the arm-shaped elements 26 and 27, this action on the door 22 actuates an advance lifting motion of the rear door 24, which goes to close the upper end of the container 14, thus preventing an access by the products contained in the shelves 10.

[0031] The entire anti-intrusion mechanism 40 described above automatically closes when falling, whenever the door 12 is no longer pushed.

[0032] Finally, there is a mechanism to actuate the blocking system 50 of the door 12. This device 50 allows blocking said door 12 during the motion of the container 14, while unblocking it only when the container 14 is in a collecting position; this is designed to prevent the user from compromising his safety by inserting his hands when the container 14 is about to move.

[0033] The mechanism 50 used to to unblock the door 12 comprises a triangular levering system 29 mounted under the door 12 itself. Said levering system 29 is connected to a spring 30 and engages a sensor 31, whenever the sliding container 14 is in a collecting position.

[0034] The levering system 29 is kept in a raised position by the extended spring 30. This position blocks

the opening of the door 12, by a stop 32 firmly affixed to the door 12 itself, as shown in Figure 5.

[0035] On the other hand, when the container 14 is in a collecting position, the levering system 29 is kept in a lowered configuration by a compressed spring, as shown in Figure 6. In this position the stop 32 of the door 12 is released from the action of the levering system 29, thus allowing said door 12 to be opened.

[0036] In order to render the unit ever more secure, a sensor 31 signalling the position of the levering system 29, and a sensor 33 designed to detect the door's opened or closed position are provided.

[0037] The engagement of the sensor 31 placed under the levering system 29 provides the machine managing system with the information that the container 14 is in a collecting position.

[0038] The other sensor 33 is set next to the door 12, and if engaged provides the information that said door 12 is closed.

[0039] The combination of the information provided by the two sensors 31 and 33 is processed by the machine managing program in such a way that as long as the door 12 remains open, the container 14 stands still, even if a request for a new product collection has arrived.

[0040] From the above description in reference to the figures it is obvious that an automatic dispensing machine according to the invention is particularly useful and advantageous. This achieves the purposes mentioned in the premise to the description.

[0041] Moreover, a unit according to the invention, designed to transport the products from the dispensing point next to a product carrying drawer up to the collecting point, may be added to an automatic dispensing machine whenever handling any products which advise its use.

[0042] By using a unit according to the invention, it is also possible to provide for the opening of several doors to collect the mentioned products, each facing a shelf of the dispensing machine. This limits the time needed to shift the sliding container, which merely needs to be moved to a position to receive the product facing the shelf holding it, without being able to revert to a fixed collecting position.

[0043] As an alternative, a single collecting door may be positioned not at a lower but at a central point of the machine, so as to minimize, on the average, the shifting motions needed between the various shelves and the machine's single collecting point.

[0044] The shapes of the automatic dispensing machine according to the invention may of course differ from those shown in the drawings, which are offered for merely exemplifying and not limiting purposes. Even the materials employed may be of a most diverse kind, ranging from plastics to metal sheets.

[0045] The scope of protection of the invention is therefore outlined by the attached claims.

Claims

1. A controlled output automatic product dispensing machine, of a type comprising a fixed structure (13) with at least one shelf (10), where at least one product-carrying drawer (11) is installed, and with at least one door (12) to catch the selected product, **characterized in that** said machine provides at least one guide (15) to slide a container (14) which collects the selected product near the corresponding product carrying drawer (11) and moves it to a collecting position accessible to the user by opening the door (12). 5 10
2. An automatic product dispensing machine according to claim 1, **characterized in that** said door (12) is fitted with an anti-intrusion system (40) which prevents accessing the product-carrying drawers (11) on the part of the user. 15 20
3. An automatic product dispensing machine according to claim 2, **characterized in that** said anti-intrusion system (40) comprises a rear door (24) which, through arm-type elements (26, 27) and pins (28), shuts off the access to the product carrying drawers (11) whenever the door (12) is opened. 25
4. An automatic product dispensing machine according to claim 1, **characterized in that** said container (14) slides on the guide (15) by a block (16) connected to the container (14) itself, and to a belt (17) moved by an electric motor (14). 30
5. An automatic product dispensing machine according to claim 1, **characterized in that** said door (12) is fitted with a blocking system (50), which prevents the access to the collecting area whenever the container (14) is not in a collecting position. 35
6. An automatic product dispensing machine according to claim 5, **characterized in that** said blocking system (50) comprises a triangular leverage system (29) and an extended spring (30), which prevents the opening of the door (12), by using a stop (32) firmly attached to the door itself, whenever the container (14) is not in a collecting position and therefore not acting to compress the spring (30). 40 45
7. An automatic product dispensing machine according to claim 1, **characterized in that** said container (14) advises the machine managing system of its position based on the information originating from a probe firmly attached to the container (14) itself, which identifies the shelves (10) of the machine. 50 55




Fig.1




Fig.2

Fig.3




Fig.4




Fig.6





Fig.5





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 02 07 6211

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (InCL7)
X	WO 00 41144 A (VDV INNOVATIETECHNIEK) 13 July 2000 (2000-07-13)	1,4,5	G07F11/42 G07F11/32
A	* abstract; claims; figures * * page 5, line 25 - page 6, line 5 * * page 6, line 32 - page 9, line 10 *	6,7	
X	GB 2 152 020 A (SANDEN CORPORATION) 31 July 1985 (1985-07-31) * the whole document *	1,4,7	
A	EP 0 581 076 A (TRANS-FINANZ-SERVICE) 2 February 1994 (1994-02-02) * abstract; claims; figures * * column 7, line 55 - column 8, line 21 *	1-3	
X,P	WO 01 24125 A (DEUTSCHE WURLITZER) 5 April 2001 (2001-04-05)	1-4	
A	* abstract; claims; figures *	5,6	
A	EP 0 866 430 A (SANDEN CORPORATION) 23 September 1998 (1998-09-23)		TECHNICAL FIELDS SEARCHED (Int.Cl.7)
A	EP 0 333 430 A (SANDEN CORPORATION) 20 September 1989 (1989-09-20)		G07F
A	US 5 439 134 A (K. TSUDA) 8 August 1995 (1995-08-08)		
A	US 4 108 333 A (L.P. FALK) 22 August 1978 (1978-08-22)		
A	WO 99 19849 A (GROSS-GIVEN MANUFACTURING COMPANY) 22 April 1999 (1999-04-22)		
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 28 August 2002	Examiner David, J
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

PPO FORM 1504/03 P2 (2/04/01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 07 6211

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

28-03-2002

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
WO 0041144	A	13-07-2000	NL	1010947 C1	06-07-2000
			NL	1012299 C2	06-07-2000
			AU	2302899 A	23-08-1999
			AU	2330800 A	24-07-2000
			DE	20000193 U1	13-07-2000
			EP	1141906 A1	10-10-2001
			EP	1055208 A1	29-11-2000
			WO	0041144 A1	13-07-2000
			WO	9940550 A1	12-08-1999
GB 2152020	A	31-07-1985	KR	9000323 Y1	30-01-1990
EP 0581076	A	02-02-1994	DE	4225165 A1	03-02-1994
			EP	0581076 A2	02-02-1994
WO 0124125	A	05-04-2001	DE	19946609 A1	12-04-2001
			AU	5682800 A	30-04-2001
			WO	0124125 A1	05-04-2001
			EP	1133760 A1	19-09-2001
EP 0866430	A	23-09-1998	JP	10241030 A	11-09-1998
			EP	0866430 A2	23-09-1998
			US	6047855 A	11-04-2000
EP 0333430	A	20-09-1989	DE	68906574 D1	24-06-1993
			EP	0333430 A2	20-09-1989
			US	4986441 A	22-01-1991
US 5439134	A	08-08-1995	JP	6290338 A	18-10-1994
US 4108333	A	22-08-1978	CA	1039245 A1	26-09-1978
WO 9919849	A	22-04-1999	US	6230930 B1	15-05-2001
			AU	9688498 A	03-05-1999
			EP	1023704 A1	02-08-2000
			WO	9919849 A1	22-04-1999
			US	6328180 B1	11-12-2001

EPC FORM P/1-9

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

THIS PAGE BLANK (USPTO)